

# Installation instructions for X-TREME ENGINE- & LINK COVER

KTM SX, 250 - 300, 2023 →  
HUSQVARNA TE 250 - 300, 2024 → / TC, 250, 2023 →  
GASGAS EC, MC, EX, 250 - 300, 2024 →



XG-2693-001



## I Scope of delivery:

- # 1x Engine & Link Cover
- # 1x attachment part A
- # 1x attachment part B
- # 1x attachment part C (motorcycle frame)
- # 1x attachment part D
- # 2x speed clips
- # 2x M6x45mm cylinder head screws
- # 2x M6x35mm hex screws
- # 1x M6x35mm countersunk screw
- # 3x M6x30mm countersunk screws
- # 2x M6x25mm countersunk screws
- # 10x washers
- # 8x M6 nuts
- # 2x sleeves
- # 2x X-GRIP stickers



## II Assembly:

The motorcycle should be clean, dry, and laid down before assembly.

- 1 Press the speed clips into attachment part C.
- 2 Position attachment part C in the front section of the motorcycle frame. (pay attention to the front and back side)
- 3 Secure attachment part C with 2x M6x45mm cylinder head screws, 4x washers, and 2x M6 nuts. The screw holes are pre-existing on the motorcycle frame.
- 4 Secure attachment parts A, B, and D to the engine cover using 6x countersunk screws, 6x washers, and 6x M6 nuts.
- 5 Hook the Engine & Link Cover on the motorcycle frame.
- 6 Adjust attachment part C on the motorcycle frame so that it aligns with the mounting holes of the Engine & Link Cover.
- 7 Press 2x sleeves into the mounting holes and secure them with 2x M6x35 hex screws.

# STAY ON TRACK